

# QUIKFLEX™ TP125



**High Speed Packaging  
System Designed for Tray  
Packaging of Loose Items  
Such as Cans and Bottles**

# QUIKFLEX™ TP125

Cans | Bottles | PET

The QuikFlex™ TP for tray packing is a high-speed packaging system for producing corrugated or paperboard trays to pack loose items such as cans and bottles. It offers flexibility to create trays with different wall heights and corner styles for ultimate efficiency and protection, as well as the versatility to work as a module for GPI's clip applicator AutoClip SplitClip™.

## Machine Features

### Machinery Highlights

#### Tool-Free Changeover

Our tool-free changeover technology is quick, simple and repeatable, eliminating time-consuming fine tuning. Our IQ tablet with changeover checklist and video help enable estimated changeover times of 15-30 minutes depending on the required change.

#### Functional Design, Easy Access

##### Construction

- Heavy-duty tubular steel frame with corrosion resistant coatings and materials
- Full height, clear visibility and sliding guard doors provide easy walk-in access to the machine

Tray Height: 2" to 6"



#### Corner Styles:

Square, rounded or bevel corners



L	15' 9"
	5850 mm
L1	10' 2"
	3110 mm
L2	8' 3"
	2510 mm
L3	33' 7"
	10230 mm
L4	28' 2"
	8590 mm
H	7' 4"
	2240 mm
W	7' 4"
	2240 mm

### Standard

- Graphic Packaging IQ Tablet - technical & parts manuals, 3D part viewer & changeover checklist
- Runs multi-diameter/height products
- No-tool, quick and repeatable changeovers
- Right or left hand carton loading and controls
- Auto prime and clean-out features
- Walk-in frame
- Text fault display
- 2.5 meter carton magazine
- Ergonomic waist-high carton loading
- Market proven segment wheel feeder
- Wedge metering for smooth product infeed
- Advanced touchscreen interface
- Hot melt glue system

### Optional

- Additional 3 meter extended tray magazine
- Change parts for additional product and/or package formats
- Custom skirting
- Coder mounting brackets
- PackFlow™ TDR5W
- Auto decaser

### Value Added Products & Services

#### Predictive Maintenance Program (PMP):

Let us manage your machine maintenance with our market-proven PMP program

### Specifications

#### Speeds up to:

Pitch	Line	Surge
15"	100ppm	125ppm

#### Tray Configurations

12, 15, 16, 18, 20, 24  
3x4, 3x5, 3x6, 4x4, 4x5, 4x6

#### Primary Container Size Ranges

Diameter: 2.1" (53mm) to 3" (76mm)  
Height: 3.4" (86mm) to 9.75" (247mm)

#### Frame Dimensions

28' 2" long, 7' 4" wide, 7' 4" high  
(8.59m x 2.24m x 2.24m)

#### Machine Weight

Approx. 22,000lbs (9,979 kg)

#### Electrical

Machine: 460 VAC, 60 Hz, 60A  
Gluer: 30A

#### Air Requirements

65 PSI-10CFM  
(4.5 bar-17 m<sup>3</sup>/h)

#### Lubrication

Automatic oiler  
Sealed bearings

